




SONGNOX[®] L570

Liquid butylated /
octylated diphenylamine
antioxidant for lubricants.

SONGWON has established a range of industry standard aminic, phenolic, phosphite and thioester antioxidants to meet the needs of the lubricant industry.

Wide range of antioxidants



Production and supply of industry standard automotive aminic, phenolic, phosphite and thioester antioxidants

Customized solutions for numerous applications


World class production facility in Asia

Comprehensive technical knowhow



Ongoing innovation to meet new industry standards and product requirements

Proven reliability



More than 50 years' manufacturing experience in South Korea

Backward integration of key raw materials

Global sales organization channels in Asia, Europe and North America

Strong commitment



Continuous investment in production facilities for aminic, phenolic and phosphite antioxidant ranges

Local supply to ensure efficient logistics

SONGNOX® L570 extends the breadth and depth of SONGWON's antioxidant product range, meeting customer requirements in the automotive and industrial sectors



SONGNOX® L570, which complements SONGWON's existing range of antioxidants, provides excellent protection against thermo-oxidative degradation of lubricating oils and greases.

Industrial end uses include mineral oil and synthetic based lubricants such as compressor, hydraulic, turbine oils and greases.

In the automotive sector, SONGNOX® L570 can be used for gasoline and diesel engine oils, gear oils, automatic transmission fluids and greases.

SONGNOX® L570 is approved by NSF / FDA for use in blending food grade lubricants with incidental food contact, at a level not to exceed 0.5% by weight.

SONGNOX® L570 is widely used in industrial as well as in automotive applications.

		Molecular Weight	Automotive			Industrial			Speciality & fuels					
			Gasoline engine oils	Diesel engine oils	ATF	Gear & axel oils	Compressor oils	Hydraulic oils	Metalworking fluids	Turbine oils	Greases	Synthetic base oils	Vegetable oils	Fuels
<p>SONGNOX® L570</p> <p>Mixture of butylated & octylated diphenylamine</p> <p>CAS No: 68411-46-1</p> <p>LQ</p>		butyl, octyl diphenylamine antioxidant	■	■	■	■	■	■	■	■	■	■	■	■
<p>SONGNOX® L135</p> <p>Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, C7-9-branched alkyl esters</p> <p>CAS NO. 125643-61-0</p> <p>LQ</p>		390	■	■	■	■	■	■	■	■	■	■	■	■

■ Recommended ■ Suitable


Storage conditions



SONGNOX® L570 antioxidant is supplied in liquid (LQ) form.

The material should be stored indoors, in closed containers, in a dry place at temperatures between 5 and 40°C.

Shelf life



SONGNOX® products are stable for 24 months, provided they are stored under the conditions described above.





For further information, please contact:

lubricantadditives@songwon.com

SONGWON provides customers with warranties and representations as to the chemical or technical specifications, compositions and/or the suitability for use for any particular purpose exclusively in individual written agreements.

The facts and figures contained herein have been carefully compiled to the best of SONGWON's knowledge but are essentially intended for informational purposes only.

SONGWON Industrial Group does not accept any liability whatsoever for any information, reference or advice provided in this document or any similar SONGWON publication.

Version 4, October 2025



It's all about **the chemistry**®

www.songwon.com