



SONGNOX® L670

Nonylated diphenylamine
antioxidant
for cutting edge
protection and security

SONGWON is a leading manufacturer of nonylated diphenylamine antioxidant.

We have extended our range of antioxidants. Industry approved, nonylated diphenylamine antioxidant SONGNOX® L670 is now available from our Asian production facility, together with SONGNOX® L135 liquid phenolic antioxidant.

The production of both SONGNOX® L670 and SONGNOX® L135 by the same manufacturer at the same facility provides customers with a new value enhancing solution. Our broad portfolio of fuel and lubes antioxidants enables us to provide solutions for numerous applications.


Thanks to its excellent physical and technical properties, SONGNOX® L670 is widely used in automotive formulations as well as many other lubricant applications.

It's all about **the chemistry™**

 **SONGWON**

SONGWON has established a range of industry standard aminic and phenolic antioxidants to meet the needs of the lubricant industry.

Wide range of antioxidants



Production of industry standard automotive aminic and phenolic antioxidants.

World class production facility in Asia.

Comprehensive technical knowhow



Continuous innovation to meet new industry standards and product requirements.

Proven reliability



More than 50 years' manufacturing experience in South Korea.

Backward integration of key raw materials.

Global sales organization channels in Asia, Europe and North America.

Strong commitment



Continued investment in production facilities for both the aminic and phenolic product ranges.

Local logistical supply.

The synergistic effects of SONGNOX® antioxidants boost performance in automotive and industrial applications

SONGNOX® L670 and SONGNOX® L135 are used together in formulations to retard oxidation in engine oils, helping to extend drain intervals, maintain viscosity, reduce deposit and foam formation, safeguard against corrosion, and protect oil at high temperatures.

SONGNOX® L670 and SONGNOX® L135 are highly suitable for the stabilization of automotive formulations such as passenger car motor oils (PCMO), heavy duty diesel engine oils (HDDEO), automatic transmission fluids (ATF) and gear oils (GO).

Other applications include compressor, gear, turbine, metal- working oils and greases, for both mineral and synthetic oils.

Aminic and Phenolic Antioxidants

SONGNOX® antioxidants suitable for automotive and other lubricant applications

		Molecular Weight	Melting Range (°C)	ATF	Compressor oils	Diesel engine oils	Fuels	Gasoline engine oils	Gear oils	Greases	Hydraulic oils	Metalworking fluids	Synthetic base oils	Turbine oils	Vegetable oils
SONGNOX® L135 4,4'-butylidenebis (6-tert-3-methylphenol) CAS NO. 125643-61-0 LQ		390	-	■	■	■		■	■	■	■	■	■	■	■
SONGNOX® L670 Bis(nonylphenyl)amine CAS No: 36878-20-3 LQ		nonyl diphenylamine antioxidant	-	■	■	■		■	■	■	■	■	■	■	■

■ Recommended ■ Suitable

Physical form



SONGNOX® L670 and SONGNOX® L135 antioxidants are supplied in liquid (LQ) form.

Storage conditions



The materials should be stored indoors, in closed containers, in a dry place at temperatures between 5 and 40°C.

Exposure to direct sunlight should be avoided.

Shelf life



SONGNOX® products are stable for 24 months, provided they are stored under the conditions described above.



For further information, please go to:

www.songwon.com

SONGWON provides customers with warranties and representations as to the chemical or technical specifications, compositions and/or the suitability for use for any particular purpose exclusively in individual written agreements.

The facts and figures contained herein have been carefully compiled to the best of SONGWON's knowledge but are essentially intended for informational purposes only.

SONGWON Industrial Group does not accept any liability whatsoever for any information, reference or advice provided in this document or any similar SONGWON publication.

Version 1, June 2017